

Microklippa

The Microklippa is very popular with estate managers and horticulturists who admire the Microklippa's fine cutting capabilities when hedge trimming and the versatility of the right or left hand cutting.

The Microklippa can be used on a range of power units from small compact tractors to small pivot steer loaders, in conjunction with a front mount kit.

Key Features

- 3.2m or 3.5m reach
- Left or Right hand cutting (swing over capability)
- Cable or Electronic Proportional Controlled (EPC) options
- Front mount option and 16-22 litres per minute.



Want to know more about the Microklippa range?

Scan the QR code to the left with a smart phone or tablet and compatible app to instantly view the page.

Alternatively visit: <http://www.bomford-turner.com/landscape/arm-mowers/microklippa/>



Cutter Bar
Ideal for trimming ornamental and standard hedgerows up to 20mm thick.



Auto swingover latch
To operate fully extend second arm, allowing single operation from left to right.



Gravity breakout
To protect tractor and machine when cutting.

Product Specification

● Standard ○ Optional — Not Available

Microklippa	3.2m (10'5")	3.5m (11'5")
Tractor requirements		
Minimum horse power	15hp	15hp
Minimum weight	550kg / 1213lbs	550kg / 1213lbs
Base unit mounting options		
Front mount	—	—
Mid-mount	—	—
Rear mount	●	●
Three point linkage (CAT II)	●	●
Axle bracket	—	—
Overall machine parameters		
Machine weight with head and oil	192kg / 423lbs	201kg / 443lbs
Capacity of oil tank	—	—
Controls		
Cable control (CC)	●	●
Electronic proportional control (EPP)	○	○
Intelligent control system (ICS)	—	—
Low pressure hydraulics (LPH)	—	—
Cable rotor reverse	—	—
Electronic rotor reverse	—	—

Microklippa	3.2m (10'5")	3.5m (11'5")
Arm features and main frame		
Telescopic arm	—	—
Telescopic arm stroke	—	—
Power slew	—	—
Power slew angle	—	—
Gravity breakout	○	○
Hydraulic breakout	—	—
Armfloat - manual	—	—
Armfloat - electronic	—	—
Headfloat - manual	—	—
Headfloat - electronic	—	—
Left hand cutting	—	—
Right hand cutting	○	○
Left and right hand cutting	○	○
Cutting heads		
Rotary Heads	—	—
1.2m and 1.5m cutterbars	○	○
Ditch Cleaner	—	—



Small but flexible
Impressive reach characteristics for a compact machine.

Working Reach

Head used for calcs: 1.2m Cutterbar

	Microklippa 3.2m (10'5")	Microklippa 3.5m (11'5")
A	3.10m / 10'2"	3.4m / 11'2"
B	3.20m / 10'6"	3.50m / 11'6"
C	2.00m / 6'6"	2.30m / 7'7"
D	3.10m / 10'2"	3.50m / 11'6"
E	4.20m / 13'9"	4.50m / 14'9"
X	1.0m / 3'4"	1.00m / 3'4"
Y	1.34m / 4'7"	1.34m / 4'7"

