

Land Levellers

The Fleming range of land Levellers have been designed as an Ideal low maintenance implement for levelling ploughed ground prior to sowing, safe guarding more expensive drilling machinery. Can also be used for levelling sand menages, gallops, horticultural use manufactured from high quality steel and finishing with a 5 stage painting process culminating in oven curing for a hard wearing finish.

Models; LL5 (1.5m), LL8 (2.5m), LL10 (3m) & LL12 (4m)

LL5

- Fully Galvanized
- For horticultural and parkland use.
- Reversible head stock for smooth option pass.
- 3 aggressive blades and 1 reversed for smooth finish.
- Cat 1 Pins
- Four off 60mm Blades
- 20-30hp



Code	LL5
Reversible	Yes
Width	1.5m
Length	0.9m
Weight	70kg
HP	20
Lift pins facility	Cat .1
Rigid/Folding	Rigid

LL8

- Galvanized Headstock Support
- Double jaw lift arm support
- 3 aggressive blades and 1 reversed for smooth finish.
- Four 80mm Blades
- Reversible head stock
- 35-75hp
- Cat 2 Lift Pins



Code	LL8
Reversible	Yes
Width	2.4m
Length	1.53m
Weight	150kg
HP	70
Lift pins facility	Cat 2
Rigid/Folding	Rigid

Land Levellers

LL10

- Galvanized Headstock Support
- Reinforced H.D frame
- Reversible head stock
- Four 80mm Heavy Duty Blades
- Double jaw lift arm support
- 75-95hp
- Cat 2 Lift Pins
- 3 aggressive blades and 1 reversed blade for smooth finish



Code	LL10
Reversible	Yes
Width	3m
Length	1.53m
Weight	250kg
HP	80
Lift pins facility	Cat 2
Rigid/Folding	Rigid

LL12



- Ideal for contracting and land reclamation.
- Raised reinforcing cross bar to allow free flow of material
- 100 Horse Power
- Heavy Duty Construction
- Double jaw support for lift arm pins
- 3 aggressive blades and 1 reversed for smooth final pass.
- Heavy Duty rams
- 80mm heavy Duty Blades
- 4m working mode, 2.5m transport mode.
- Cat 2 Lift Pins

Code	LL12
Reversible	No
Width	4m
Length	1.5m
Weight	900kg
HP	100+
Lift pins facility	Cat 2
Rigid/Folding	Folding



Transport Position
2.5m wide